

SECURITHERM sequential thermostatic shower mixer

Ref. 9630

Thermostatic mixer with no non-return valves, bottom outlet



DESCRIPTION

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

SECURITHERM sequential thermostatic shower mixer.

Sequential thermostatic mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between the hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant sequential thermostatic cartridge adjusts the flow rate and the temperature.

Temperature adjusts from cold water up to 39°C with temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior (reduces bacterial proliferation).

Flow rate regulated at 9 l/min.

Chrome-plated brass body and Hygiene lever L. 100mm.

M1/2" bottom outlet.

Mixer with no wall connectors with filters integrated in the inlets, F3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

Technology	SECURITHERM Securitouch sequential thermostatic shower mixer
Length	184mm
Flow rate	9 lpm at 3 bar
Temperature limiter	YES
Finish	Chrome-plated brass
Norms	     
Warranty	
Repairability	

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimum anti-scalding safety



Thermostatic: temperature stability

