

Wall-mounted sequential mechanical basin mixer

Ref. 2436

Sequential mechanical mixer with swivelling spout



DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2436

Wall-mounted sequential mechanical basin mixer.
Sequential over 90°: opens and closes with cold water.
Flat swivelling under-spout, L. 200mm, with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
Securitouch thermal insulation prevents burns.
Ø 35mm ceramic cartridge.
Pre-set maximum temperature limiter.
Body and spout with smooth interiors and low water volume. (reduces bacterial development).
Flow rate regulated at 5 lpm.
Hygiene lever L. 150mm.
Supplied with 2 wall-mounted STOP/CHECK connectors, M1/2" M3/4".
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2436

Connector	M1/2"
Technology	Sequential mechanical mixer
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

ADVANTAGES

-  Sequential: opens and closes with cold water
-  Maximum hygiene: manages biofilm
-  No non-return valves
-  No manual contact: Hygiene lever

