Wall-mounted sequential mechanical basin mixer

Ref. 2436S

Sequential mechanical mixer with swivelling spout



DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2436S

Sequential mechanical basin mixer.

Sequential over a 90° range: opens and closes with cold water.

Flat swivelling under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Securitouch thermal insulation prevents burns.

Ø 35mm ceramic cartridge.

Pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Hygiene lever L. 150mm.

Supplied with 2 wall-mounted standard connectors, M1/2" M3/4".

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2436S

M1/2"
Sequential mechanical mixer
200mm
5 lpm
YES
Chrome-plated brass
30 g
50 g REPARABILITY

ADVANTAGES



Sequential: opens and closes with cold water




Maximum hygiene: manages biofilm



No non-return valves



No manual contact: Hygiene lever



© DELABIE https://www.delabie.com