

TEMPOMIX shower mixer - lead-free

Ref. 790425LF

Single control time flow, lead-free



DESCRIPTION

TEMPOMIX shower mixer - lead-free - Ref. 790425LF

Recessed time flow shower mixer:
 Stainless-steel wall plate 160 x 160.
 Standard recessed waterproof housing.
 Recessing depth adjustable from 28 to 48 mm.
 TEMPOMIX 3/4" single control shower mixer.
 Ligature-resistant collar.
 Temperature control and operation via the control.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 12 lpm at 3 bar.
 M1/2" connectors for Ø 15mm copper tails.
 Integrated non-return valves and filters.
 Chrome-plated metal control. Lead-free.
 30-year warranty.
 This sanitary ware model is not supplied with recessed waterproof housing, the installer must ensure the impermeability of recessed housing as well as draining any potential leaks and condensation (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX shower mixer - lead-free - Ref. 790425LF

Connector	M1/2" Ø 15mm
Height	160 mm
Width	160 mm
Flow rate	12 lpm
Warranty	

ADVANTAGES



Lead-free



Installation recessed in the wall



System tested to over 500,000 operations

