

BIOSAFE mechanical basin mixer - lead-free version

Ref. 2621LF

Single hole mechanical mixer with no spout H.95 L.110, lead-free

DESCRIPTION

BIOSAFE mechanical basin mixer - lead-free version - Ref. 2621LF

Deck-mounted mechanical basin mixer, lead-free version.
 Single hole mechanical mixer H.95 L.110.
 No spout: hygienic flow straightener integrated into the body.
 Securitouch thermal insulation prevents burns.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Thermal shocks are possible without removing the control lever or shutting off the cold water.
 Mixer body has smooth interior and low water volume (reduces bacterial development).
 Flow rate pre-set at 4 lpm.
 Solid control lever.
 No pop-up waste.
 F3/8" rotating PEX flexibles.
 Fixing reinforced by two stainless-steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care facilities, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

BIOSAFE mechanical basin mixer - lead-free version - Ref. 2621LF

Connector	F3/8"
Technology	Mitigeur mécanique BIOSAFE
Height	180 mm
Length	220 mm
Drop height	95 mm
Spout length	110 mm
Flow rate	4 l/min
Temperature limiter	OUI
Warranty	



ADVANTAGES

-  Hygiene: body with very low water volume
-  Maximum hygiene: no spout
-  Lead-free
-  Thermal shocks without removing control lever

