

BIOSAFE mechanical basin mixer - lead-free version

Ref. 2921TLF

Single hole mechanical mixer H.100 L.110 - lead-free

DESCRIPTION

BIOSAFE mechanical basin mixer - lead-free version - Ref. 2921TLF

Deck-mounted mechanical basin mixer, lead-free.
 Single hole mixer with spout H.100 L.110 fitted with a BIOSAFE hygienic outlet. Outlet suitable for fitting a BIOFIL terminal filter.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Spout with internal tube with smooth interior and very low water volume.
 The speed of the water inside this tube reduces biofilm development considerably.
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
 Body with very low water volume (reduces bacterial development).
 Flow rate pre-set at 5 lpm.
 Solid control lever.
 No pop-up waste.
 F3/8" PEX flexibles.
 Fixing reinforced by 2 stainless-steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care facilities, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

BIOSAFE mechanical basin mixer - lead-free version - Ref. 2921TLF





Connector	F3/8"
Technology	BIOSAFE mechanical mixer
Drop height	100 mm
Spout length	110 mm
Flow rate	5 lpm
Temperature limiter	OUI
Finish	Chrome-plated brass

Norms 

Warranty 



ADVANTAGES

-  Hygiene: body with very low water volume
-  Thermal shock without removing control lever
-  Lead-free
-  Pre-set maximum temperature limiter

