

# Pressure-balancing SECURITHERM EP BIOSAFE basin mixer

Ref. 2921TEPLF

Single hole mechanical mixer H.100 L.110 - lead-free

## DESCRIPTION

**Pressure-balancing SECURITHERM EP BIOSAFE basin mixer - Ref. 2921TEPLF**

Deck-mounted mechanical mixer with pressure-balancing, lead-free. Single hole mixer with spout H.100 L.110 with a BIOSAFE hygienic outlet. Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 35mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of variations in pressure and flow rate.

Spout with a tube with a smooth interior, no niches where bacteria can develop, and low water volume.

The speed with which the water flows through the tube considerably reduces biofilm development.

Thermal shocks are possible without removing the lever or shutting off the cold water supply.

Body with very low water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Solid control lever.

No pop-up waste.

F3/8" PEX flexibles with filters and non-return valves.

Fixing reinforced by 2 stainless-steel rods.

SECURITHERM pressure-balancing mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Pressure-balancing SECURITHERM EP BIOSAFE basin mixer - Ref. 2921TEPLF**

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Connector           | F3/8"                                                                               |
| Technology          | SECURITHERM EP BIOSAFE mechanical mixer                                             |
| Drop height         | 100 mm                                                                              |
| Spout length        | 110 mm                                                                              |
| Flow rate           | 5 lpm                                                                               |
| Temperature limiter | OUI                                                                                 |
| Finish              | Laiton chromé                                                                       |
| Warranty            |  |



## ADVANTAGES



HW flow rate is reduced if CW supply fails



Hygiene: body with very low water volume



Lead-free



Thermal shocks without removing control lever

