

TEMPOMATIC 4 urinal valve

Ref. 430PBOX-430036

Electronic, battery-operated



DESCRIPTION

TEMPOMATIC 4 urinal valve - Ref. 430PBOX-430036

Electronic valve for waterproof, recessed individual urinals:
123 6V Lithium battery-operated.

Black wall plate 145 x 145mm in shock-resistant vitro-ceramic glass with integrated electronics.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, filter and solenoid valve are all integrated and accessible from the front.
- TEMPOMATIC 4 urinal valve F 1/2" is compatible with sea water and grey water.
- Supplied in 2 kits: secure system flush without sensitive elements.
- Shock-resistant infrared presence detection sensor.

Detection delay is 10 seconds.

3 programmes (rinsing volume can be set according to urinal type).

High-frequency mode (exclusive to DELABIE):

- Short rinse after each user.
- Additional rinse at the end of the busy period.

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use: prevents vacuums.

Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted.

Connection with Ø 35mm connection washer (for standard urinals) or 1/2" brass connection (for urinals supplied by flexible).

For use with neck tube 752430 or 757430.

10-year warranty.

ADVANTAGES



3 rinse programmes and high-frequency mode



Total hygiene: no manual contact



Hygienic duty flush



Waterproof housing, adjustable and modular

TECHNICAL FEATURES

TEMPOMATIC 4 urinal valve - Ref. 430PBOX-430036

Connector	F1/2"
Technology	Electronic
Height	145mm
Depth	83 - 190mm
Width	145mm
Flow rate	0.15 l/sec
Warranty	

